

CHF1664DGT-GAS

 **CHEF** Line



Forno a gas combinato convezione vapore 16 teglie 600 x 400 mm con pannello digitale touch con tecnologia BLACK MASK

Gas combi oven 16 trays 600 x 400 mm with digital touch panel with BLACK MASK technology



Plus

Sistema carter d'aria brevettato **Airflowlogic™**
Sistema vapore diretto brevettato **Humilogic™**

Software per gestione dell'umidità
Accensione forno programmabile
N° 40 ricette memorizzate
Sistema per HACCP
Cerniere porta regolabili
Regolamento 2016/426/UE

Dotazione di serie

Imballo cartone+pallet (LxPxH mm) 1146 x 1385 x 2140 mm
Cavo Monofase [3G 1,5]-L=1600 mm
Presenza USB
Predisposizione sonda al cuore
Predisposizione lavaggio automatico
Cerniera con bloccoporta per aperture regolate a 60°, 90°, 120°, 180°
Carrello estraibile con impugnatura e ruote dotate di freno cod. CHCR16TC
Ugello GPL

Dimensioni

Dimensioni (LxPxH mm) 930 x 1160 x 2060
Peso (kg) 277,2
Passo guide (mm) 80

Caratteristiche elettriche

Portata termica (kW) 30
Frequenza (Hz) 50/60
Voltaggio (V) AC 220/230
N° motori 4 bidirezionali
Generatore di vapore (kW) /
Protezione acqua IPX4

Caratteristiche funzionali

Alimentazione Multigas (collaudo a metano)
Capacità N° 16 teglie/griglie 600 x 400 mm
Cottura Semistatica + ventilata
Vapore Diretta con regolazione automatica attraverso selettore touch (10 steps)
Camera di cottura Acciaio AISI 304
Temperatura 30 - 260 °C
Controllo temperatura 2 Sonde digitali
Pannello comandi Black mask electronic control
N° programmi 100
Fasi programmabili 10
Temperatura preimpostata 180 °C
Preriscaldamento Disponibile
Apertura laterale dx
Ventilata
Porta Vetro ispezionabile
Piedini Regolabili



Plus

Patented fan guard system **Airflowlogic™**
Patented system for direct steam **Humilogic™**

Humidity management software
Programmable oven start
N° 40 recipes stored
HACCP system
Adjustable door hinges
Regulation 2016/426/UE

Equipment

Cardboard box dimensions with pallet (WxDxH mm) 1146 x 1385 x 2140 mm
Cable Single-phase [3G 1,5]-L=1600 mm
USB port
Core probe predisposition
Automatic washing system predisposition
Hinge with door locking for openings adjusted at 60°, 90°, 120°, 180°
Trolley with removable handle and braked wheels cod. CHCR16TC
Nozzle for LPG

Dimensional features

Dimensions (WxDxH mm) 930 x 1160 x 2060
Weight (kg) 277,2
Distance between rack rails (mm) 80

Electrical features

Thermal supply (kW) 30
Frequency (Hz) 50/60
Voltage (V) AC 220/230
N° motors 4 bidirectionals
Boiler (kW) /
Protection against water IPX4

Functional features

Power Multigas (tested for natural gas)
Capacity N° 16 trays/grids 600 x 400 mm
Type of cooking Semistatic + ventilated
Steam Direct steam controlled by touch screen (10 levels.)
Cooking chamber AISI 304 stainless steel
Temperature 30 - 260 °C
Temperature control 2 Digital probe thermometers
Control panel Black mask electronic control
N° programs 100
Programmable cooking steps 10
Pre-heating temperature 180 °C
Pre-heating function Programmable
Right side opening
Ventilated
Door Inspectionable glass
Feet Adjustable